

Water Cut-Off Mastic

Available in 10.5 oz. fiber caulk tubes or 5 gallon pails

Product Information

LionGUARDTM Water Cut-Off Mastic is a gray solvent based caulk designed to be used under the membrane to prevent water infiltration.

Meets OTC VOC requirements.

Application Instructions:

Water Cut Off Mastic is gray colored and meant to be used UNDER single ply membranes such as EPDM and TPO as a preventative measure to stop water from entering the roof system. It is very sticky. It is NOT UV protective, so installation under the membranes is vital for the long term performance of this product. Use at all drains and penetrations. Can also be used in reinforced membrane systems to prevent water from wicking into the scrim of all membranes. Always use under membranes only.

Physical Properties: Color: Gray Density (#/GAL.): 11.0# Flash Point (F): 14 F TCC Solvent System: Aliphatic Storage: May be stored outside if protected from water.

Viscosity (eps): 40# .104= 15-20 sec./20 gms. Sievers Rheometer % Solids: 86 Base: Synthetic elastomers, resin(s) and filler(s) Clean-up Solvent: Mineral spirits, VMP naptha, kerosene Packaging: 5 gallon pails, 10.5 oz. fiber caulk tubes (10 or 25 tubes/ctn)

Hazards: Extremely flammable. Avoid repeated skin contact or the breathing of concentrated vapors. Use in well ventilated areas away from heat, sparks, fire, flame and ignition sources. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back. Do not inhale vapors above TLV as listed on the MSDS. **Freight Classification:** UN1133, ADHESIVE, 3 PGII NMFC# 170060 CLASS 55

NOTE: TECHNICAL INFORMATION AND DATA SHOULD BE CONSIDERED REPRESENTATIVE OR TYPICAL ONLY AND SHOULD NOT BE USED FOR SPECIFICATION PURPOSES.

User's Responsibility

This Product Information cannot cover all possible situations, which the user may experience during processing. Each aspect of your operations should be examined to determine if, or where, additional precautions may me necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee instructional programs for your operation

Disclaimer of Liability

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, express or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained form the use thereof. Compliance with all applicable