

SAFETY DATA**1. CHEMICAL PRODUCT & MANUFACTURER:**

SealCorpUSA, Inc.
1175 E Diamond Ave
Evansville, IN 47711
812-868-0790 FAX 812-868-0789

PRODUCT: LionGUARD LG-LC40 Black Lap Caulk
GHS PRODUCT ID: LionGUARD LG-LC40 Black Lap Caulk
Recommended for use as: Roofing Sealant
Restrictions on use:

PRODUCT NAME: LionGUARD LG-LC40 Black Lap Caulk
CHEMICAL FAMILY: HYDROCARBON

MANUFACTURER/DISTRIBUTOR: SAME AS ABOVE
TELEPHONE: SAME AS ABOVE

24 HOUR EMERGENCY CONTACT NUMBER: PERS 1-800-728-2482 PERS ID# 10267

2. HAZARDS IDENTIFICATION:

Physical hazards
Health hazards

Flammable liquids	Category 3
Acute toxicity, dermal	Category 4
Serious Eye Damage/eye irritation	Category 2
Acute toxicity, inhalation	Category 4
Carcinogenicity	Category 2
Skin corrosion/irritation	Category 2
Specific target organ toxicity, single exposure	Category 3 respiratory irritation
Specific target organ toxicity, single exposure	Category 3 narcotic effects
Specific target organ toxicity, repeated exposure	Category 2
Aspiration hazard	Category 1
Not classified	
Not classified	

Environmental hazards
OSHA defined hazards
Label elements



Signal word

DANGER

Hazard statement

Flammable liquid and vapor. (H226)
Causes skin irritation. (H315)
Harmful in contact with skin (H312)
May be fatal if swallowed and enters airways. (H304)
Harmful if inhaled (H332)
May cause respiratory irritation. (H335)
May cause drowsiness or dizziness. (H336)
Causes serious eye irritation (H319)
May cause damage to organs through prolonged or repeated exposure (H373)
Suspected of causing cancer (H351)

Precautionary Statement**Prevention**

Do not get in eyes, on skin, or on clothing	(P262)
Avoid breathing vapor or mist	(P261)
Do not handle until all safety precautions have been read and understood	(P202)
Keep away from heat/sparks/open flames/hot surfaces– No smoking	(P210)
Keep container tightly closed	(P233)
Ground/bond container and receiving equipment	(P240)
Use explosion-proof electrical/ventilating/lighting equipment	(P241)
Use only non-sparking tools	(P242)
Take Precautionary measures against static discharge	(P243)
Wash thoroughly after handling	(P264)
Use only outdoors or in a well-ventilated area	(P271)
Do not eat, drink or smoke when using this product	(P270)
Wear protective gloves/protective clothing/eye protection/face protection	(P280)

Response

IF SWALLOWED: Immediately call a poison center/doctor. (P301 + P310)

Do NOT induce vomiting. (P331)

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing (P304 + P340)

If on skin (or hair): Remove/Take-off immediately all contaminated clothing. Rinse skin with water/shower. (P303+ P361+P353)

If skin irritation occurs: Get medical advice/attention (P332 + P 313)

If exposed or concerned: Get medical advice/attention (P308 + P313)

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305 + P351 + P338)

If eye irritation persists: Get medical advice/attention (P337 + P313)

In case of fire: Use NFPA Class B extinguishers. If water is used, use fog nozzles. (P370 + P378)

Storage

Keep cool (P235)

Store in well-ventilated place. Keep container tightly closed. (P403 + P233)

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. (P501)

3. COMPOSITION & PRODUCT INFORMATION ON HAZARDOUS INGREDIENTS:

Chemical Name	Common name, Synonyms	CAS#	% by weight
Xylene (Mixed isomers)		1330-20-7	> 29.52
Ethyl Benzene		100-41-4	< 7.38

4. FIRST AID MEASURES:

INHALATION: REMOVE TO FRESH AIR IF OVERCOME. IF BREATHING HAS STOPPED BEGIN CPR. CALL A PHYSICIAN AT ONCE.

EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES.

SKIN CONTACT: WASH WITH HAND CLEANER; FOLLOW WITH SOAP AND WATER.

INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN AT ONCE.

NOTE TO PHYSICIAN: CONTAINS PETROLEUM DISTILLATES.

PRIMARY ROUTES OF ENTRY: INHALATION, SKIN

5. FIRE FIGHTING MEASURES:

FLASHPOINT, TAG CLOSED CUP: 80.6 F (27 C)

GENERAL HAZARD: HIGHLY FLAMMABLE. MAY FORM COMBUSTIBLE OR EXPLOSIVE MIXTURES WITH AIR. CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL CONSIDERABLE DISTANCES TO IGNITION SOURCES AND FLASH BACK.

FIRE FIGHTING INSTRUCTIONS: WATER SPRAY MAY BE INEFFECTIVE BUT MAY BE USED TO COOL CLOSED CONTAINERS. IF WATER IS USED, USE FOG NOZZLES.

FIRE FIGHTING EQUIPMENT: NFPA CLASS B EXTINGUISHERS (CO₂, FOAM, DRY CHEMICAL) AND SELF-CONTAINED BREATHING APPARATUS.

COMUSTION PRODUCTS: SMOKE, NORMAL COMBUSTION PRODUCTS.

6. ACCIDENTAL RELEASE MEASURES:

LAND SPILL: REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE MATERIAL WITH ABSORBENTS AND/OR NON-SPARKING TOOLS.

WATER SPILL: USE ABSORBENT BOOMS TO DIKE AREA AND MINIMIZE AREA OF CONTAMINATION.

7. STORAGE AND HANDLING:

STORAGE TEMPERATURE: AMBIENT
STORAGE PRESSURE: ATMOSPHERIC

GENERAL: KEEP MATERIAL AWAY FROM HEAT, SPARK AND OPEN FLAME. DO NOT STORE IN OPEN OR UNLABELED CONTAINERS. USE WITH ADEQUATE VENTILATION. DO NOT STORE ABOVE 120°F. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUIDS. DO NOT CUT, BRAZE OR WELD. *FOR INDUSTRIAL USE ONLY*. KEEP OUT OF THE REACH OF CHILDREN. READ PRODUCT LABEL AND OBSERVE ALL PRECAUTIONS BEFORE USE.

8. EXPOSURE CONTROL/PERSONAL PROTECTION:**Occupational Exposure Limits**

Ethyl Benzene (CAS 100-41-4)	ACGIH TWA	20 ppm
	PEL	100 ppm 435 mg/m ³
Xylene (CAS 1330-20-7)	NIOSH STEL	150 ppm 655 mg/m ³
	TWA	100 ppm 435 mg/m ³

ENGINEERING CONTROLS: LOCAL EXHAUST: PREFERABLE
MECHANICAL EXHAUST: ACCEPTABLE-USE ONLY
CLASS I GROUP D APPROVED DEVICES.

PERSONAL PROTECTION: OSHA PEL: 100 ppm 435 mg/m³
RESPIRATORY PROTECTION: VENTILATE TO KEEP VAPORS BELOW THRESHHOLD LIMIT
VALUES. NIOSH APPROVED RESPIRATORS FOR AREAS OF CONCENTRATED VAPORS.
EYES: SPLASH GOGGLES FOR LIQUID PRODUCTS
GLOVES: MUST BE IMPERVIOUS TO SOLVENTS

Exposure Guidelines

9. PHYSICAL AND CHEMICAL PROPERTIES:

SPECIFIC GRAVITY:	1.085	FLASH POINT: TAG CLOSED CUP:	80.6 F (27 C)
DENSITY:	9.05	VAPOR PRESSURE AT 20C (MM OF HG):	6.82
VAPOR DENSITY:	3.66	(VOC) CONTENT:	400.4 g/liter
EVAPORATION RATE (nBuAc=1):	.51	APPEARANCE:	Black paste
SOLUBILITY IN WATER:	INSOLUBLE	ODOR:	Aromatic solvent
BOILING RANGE (F):	278/290	ODOR THRESHOLD:	Unknown
PHYSICAL STATE:	Paste/liquid	PH:	Not available
% VOLATILE BY VOLUME:	46.13	MELTING POINT/FREEZING POINT:	Not determined
AUTOIGNITION TEMPERATURE:	Not determined	PARTITION COEFFICIENT:	n-octanol/water 3.2
DECOMPOSITION TEMPERATURE:	Unknown		
EXPLOSIVE/FLAMMABLE LIMITS: (LEL): 1% (UEL): 7% est.			

10. STABILITY AND REACTIVITY:

GENERAL: THIS PRODUCT IS STABLE AND HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID: AVOID STRONG OXIDIZING AGENTS. AVOID ALL SOURCES OF IGNITION. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL A CONSIDERABLE DISTANCE TO AN IGNITION SOURCE AND FLASHBACK.

HAZARDOUS DECOMPOSITION PRODUCTS: NONE

11. TOXICOLOGICAL INFORMATION:

Carcinogenicity: Xylene Mixed Isomers (CAS 1330-20-7) IARC Monographs 3 Not classifiable as to carcinogenicity to humans
Ethyl benzene (CAS 100-41-4) IARC Monographs 2B Possibly carcinogenic to humans.

HEALTH EFFECTS:

LIKELY ROUTES OF EXPOSURE: skin absorption, inhalation

DELAYED AND IMMEDIATE CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

Skin: Dry skin, dermatitis, de-fatting of the skin with chapping and cracking

Inhalation: Inebriation, followed by headache and nausea. Dizziness, convulsions and unconsciousness in sever cases.
Anorexia and nervousness may persist for several months following acute overexposure. Components in this product
Have been shown to cause firth defects and reproductive disorders in laboratory animals.

(ACUTE TOXICITY ESTIMATE): May be fatal if swallowed and enters airways

12. ECOLOGICAL INFORMATION:

AQUATIC AND/OR TERRESTRIAL EXOTOXICITY:

Not classified as environmentally hazardous.

PERSISTENCE AND DEGRADABILITY:

No data available

BIO ACCUMULATIVE POTENTIAL:

Partition coefficient n-octanol/water (log Know) 3.15-3.20

13. DISPOSAL CONSIDERATIONS:


THIS MATERIAL IS CONSIDERED A HAZARDOUS WASTE FOR DISPOSAL PURPOSES. SEE 40 CFR PART 261.7 FOR FURTHER INFORMATION CONCERNING THE DISPOSITION OF EMPTY CONTAINERS. HAZARDOUS WASTES MAY NOT BE LANDFILLED! REFER TO 40 CFR PART 261 SUBPART C FOR DEFINITIONS OF HAZARDOUS WASTE.

14. TRANSPORTATION INFORMATION:U.S. Department of Transportation (DOT)

Shipping Description:	UN1133, Adhesives, 3, PGIII
Non-Bulk Package marking:	Adhesives, UN1133
Non-Bulk Package labeling:	Flammable liquid
Packaging references:	49 CFR 172.101 adhesives containing a flammable liquid
Exceptions:	173.150 Consumer commodity LQ-label no other marking required
Special Provisions:	149 Limited Quantity, Except for AIR
Hazardous Substance:	See section for RQ's if applicable
Emergency Response Guide:	128



SPECIAL SHIPPING INFORMATION: WHEN PACKAGED IN CAULKING TUBES IN TESTED, CARDBOARD OUTER CARTONS WEIGHING < 66 POUNDS, THIS MATERIAL MAY BE SHIPPED PER HM-215K AS A LIMITED QUANTITY. SHIPPED AS A LIMITED QUANTITY, A LIMITED QUANTITY SHIPPING LABEL IS REQUIRED ON THE CARTON ONLY. OTHER SPECIAL DESCRIPTIONS, MARKS, LABELS OR PLACARDS ARE NOT NECESSARY AND THE MATERIAL MAY BE DESCRIBED ON THE BILL OF LADING BY PRODUCT NAME RATHER THAN PROPER SHIPPING DESCRIPTION.



LIMITED QUANTITY LABEL
(Actual size is 100mm X 100mm)

International Maritime Dangerous Goods (IMDG)

Shipping Description:	UN1133, Adhesives, 3, PGIII
Non-Bulk Package marking:	Adhesives, UN1133
Labels:	Flammable liquid
Packaging-Non-Bulk:	P001 UN MODEL RULES ALSO: 49 CFR 172.101 adhesives containing a flammable liquid
Exceptions:	PP1 UN MODEL RULES ALSO: 173.150 Consumer commodity LQ-label no other marking required
EMS:	
Marine Pollutant:	No

International Civil Aviation Org./International Air Transport Assoc. (ICAO/IATA)

UN/ID #:	UN1133
Proper Shipping Name:	Adhesives
Hazard Class/Division:	3
Subsidiary risk:	
Packing Group:	III
Non-Bulk Package marking:	Adhesives, UN1133
Labels:	Flammable liquid
Exceptions:	UN/ID#8000 Consumer commodity Limited Quantity for air label
ERG Code:	128

15. REGULATORY INFORMATION:

OSHA STATUS: HAZARDOUS

CERCLA HAZARDOUS SUBSTANCES LIST: Listed

SARA TITLE III:

SECTION 302: EXTREMELY HAZARDOUS SUBSTANCES: NONE

SECTION 311/312: 311-YES 312-YES

SECTION 313: Contains >29.52 % Xylene (mixed isomers) which is a reportable Section 313 chemical

SECTION 313: Contains < 7.38 % Ethyl benzene which is a reportable Section 313 chemical

RCRA STATUS: IF DISCARDED IN ITS PURCHASED FORM, THIS PRODUCT IS A RCRA HAZARDOUS WASTE. IT IS THE RESPONSIBILITY OF THE PRODUCT USER TO DETERMINE AT THE TIME OF DISPOSAL, WHETHER A MATERIAL CONTAINING THE PRODUCT OR RESIDUE OF THE PRODUCT REMAINS CLASSIFIED A HAZARDOUS WASTE AS PER 40 CFR 261, SUBPART C. STATE OR LOCAL REGULATIONS MAY ALSO APPLY IF THEY DIFFER FROM THE FEDERAL REGULATION.



WARNING: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or Other reproductive harm. For more information go to : www.P65warnings.ca.gov.

TSCA Status: All materials contained in this product are TSCA listed.

Canadian Status: All materials contained in this product are listed on the Canadian Domestic Substance List.

European Union Status: All materials contained in this product are listed on EINECS.

Australia: Listed on AICS.

China: Listed on IECSC.

Japan: Listed on ENCS.

Korea: Listed on ECL.

New Zealand: Listed on New Zealand Inventory.

Philippines: Listed on PICCS.

Taiwan: Listed on TCSI

16. OTHER INFORMATION:

APPROVAL DATE: 10-30-24

SUPERSEDES DATE: 8-27-2018

REASON FOR REVISION: NEW GHS EXTENDED FORMAT

MSDS FORMAT: GHS extended format

THE INFORMATION HEREIN IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE CORRECT AS OF THE DATE HEREOF. INFORMATION IS BASED UPON SUPPLIER-ISSUED SAFETY DATA SHEETS AND MAY BE SUBJECT TO ERROR. IF APPRISED OF CHANGES, UPDATED SDS WILL BE PROMPLY ISSUED. USERS MUST MAKE THEIR DETERMINATION REGARDING THE SUITABILITY OF THE PRODUCT FOR THEIR OWN PURPOSES PRIOR TO USE. THE MANUFACTURER CANNOT ANTICIPATE ALL CONDITIONS UNDER WHICH THIS INFORMATION AND ITS PRODUCT MAY BE USED.

READ PRODUCT LABEL CAREFULLY BEFORE USE AND FOLLOW ALL PRECAUTIONS.
END OF SDS